Impoundment
Inspecto:(E)

W1578510001-01

ange	17/2	186h	Port-
ange	lo f	uechi	you

Weather rainy

·	İtem	Condition	Comments
	Vertical & Horizontal Alignment of Crest	GC	
	Riprap	GC	
	Seepage	NE	
	Erosion	NE	
	Filter and Filter Drains	NA	
	Unusual Movement or Cracking At or Beyond Toe	NE	
	Surface Cracks	NE	
Embankment	Sloughing or Erosion of Outer Embankment Slopes	NE	
Embar	Sloughing or Erosion of Inner Embankment Slopes	NE	
,,,,,,	Upstream Face Slope Protection (HDPE Liner)	NA	
	Upstream Face Slope Protection (Riprap)	GC	
	Animal Damage	NE	
	HDPE Liner	NA	
	Vegetative Cover	GC	needs mowed
	Condition of Plezometers	GC GC	
	Embankment Drainage Ditches	GC	

۰	A : .	tion	0-	J
. (1)		пол	1.0	100

EC = Emergency Condition. A serious dam safety condition exists that needs immediate action.	 Report immediately to Chief Dam Safety Engineer and immediate supervisor
--	--

IM = Item needing immediate maintenance to restore or ensure its safety or integrity. Remediation should be completed within 1 month.

MM = Item needing minor maintenance. The safety or integrity of the item is not yet imperiled.

OB = Condition requires regular observation to ensure that the condition does not become worse.

GC = Good Condition.

NE = No evidence of a problem.

NI = Not Inspected. Reason should be stated in comment.

Impoundment East Fly Ash Pond Page 1 of 2

i			
	Drains/Weeps	. NA	
	Discharge coloration	NA	no discharge
	Seepage	NE	
_	Allgnment	GC	
Spillway	Bridge and Piers	NA	
S	Fencing	NA	
	Construction Joints	NA	
	Trash Racks	NA	
	Differential Settlement	NA	
	Stop Logs	NA	· · ·
tor	Riprap .	GC	
Energy Dissipator	Outlet Channel	GC	
ergy D	Concrete Condition	NA	
Ep	Debris	NE	
	Alignment	NA	
cture	Connection to Bollard	NA	
Decant Structure	Debris in Inlets	NA	
Decal	Condition of Pipe (60" culvert)	GC	
	Seepage at Inlet or Outlet	NA	

Condition Codes

EC = Emergency Condition. A serious dam safety condition exists that needs immediate action. Report immediately to Chief Dam Safety Engineer and immediate supervisor

IM = Item needing immediate maintenance to restore or ensure its safety or integrity. Remediation should be completed within 1 month.

MM = Item needing minor maintenance. The safety or integrity of the item is not yet imperiled

OB = Condition requires regular observation to ensure that the condition does not become worse

GC = Good Condition

NE = No evidence of a problem.

NI = Not Inspected. Reason should be stated in comment.

Imposition (c)

W1578510001-02 W1578510001-03

SFAP			
4-28			
angus	vect	Mel	4
, ,			į
			1

	66°
Westlic	rainu
	7

	Item	Condition	Comments
	Vertical & Horizontal Alignment of Crest	GC	
	Riprap	GC	
	Seepage	NE	
	Erosion	NE	
	Filter and Filter Drains	GC	
	Unusual Movement or Cracking At or Beyond Toe	NE	
+-	Surface Cracks	NE	
Embankment	Sloughing or Erosion of Outer Embankment Slopes	NE	
Embar	Sloughing or Erosion of Inner Embankment Slopes	NE	
_	Upstream Face Slope Protection (HDPE Liner)	NA	
	Upstream Face Slope Protection (Riprap)	GC	
	Animal Damage	NE	
	HDPE Liner	NA	
	Vegetative Cover	GC	needs moned
	Condition of Piezometers	GC GC	
	Embankment Drainage Ditches	GC	

han'	itlan.	Codes	

EC = Emergency Condition. A serious dam safety condition exists that needs immediate action. Report immediately to Chief Dam Safety Engineer and imme	diate supervisor
---	------------------

IM = Item needing immediate maintenance to restore or ensure its safety or integrity. Remediation should be completed within 1 month.

MM = item needing minor maintenance. The safety or integrity of the item is not yet imperiled.

OB = Condition requires regular observation to ensure that the condition does not become worse.

GC = Good Condition.

NE = No evidence of a problem.

NI = Not Inspected. Reason should be stated in comment.

Impoundment SFAP Page 1 of 2

	Drains/Weeps	GC	
	Discharge coloration	GC NA	no discharge
!	Seepage	NE	
	Alignment	NA	
Spillway	Bridge and Piers	NA	
S	Fencing	NA	
	Construction Joints	NA	
	Trash Racks	NA	·
	Differential Settlement	NA	
	Stop Logs	NA	
tor	Riprap	GC	**************************************
Energy Dissipator	Outlet Channel	GC	
ergy D	Concrete Condition	NA	
Ë	Debris	NE	
	Alignment	GC	
Decant Structure	Connection to Bollard	NA	
	Debris In Inlets	NE	
Decar	Condition of Pipe	NA	
	Seepage at Inlet or Outlet	NE	

Condition Codes

EC = Emergency Condition. A serious dam safety condition exists that needs immediate action. Report immediately to Chief Dam Safety Engineer and immediate supervisor

IM = Item needing immediate maintenance to restore or ensure its safety or integrity. Remediation should be completed within 1 month.

MIM = Item needing minor maintenance. The safety or integrity of the item is not yet imperiled.

OB = Condition requires regular observation to ensure that the condition does not become worse.

GC = Good Condition.

NE = No evidence of a problem.

NI = Not Inspected. Reason should be stated in comment.

Tagavaduant Side

Inspector(s)

W1578510001-06

Bottom Ach Pond 4-28-21 angla Lucchful

7.680.p.1. h.c.	: Go°
Weather	rainy

ltem	Condition	Comments
Vertical & Horizontal Alignment of Crest	GC.	
Riprap	GC.	
Seepage	NE	
Erosion	NE	
Filter and Filter Drains	NA	
Unusual Movement or Cracking At or Beyond Toe	NI	Area under water
Surface Cracks	NE	
Sloughing or Erosion of Outer Embankment Slopes	NE NE	
Sloughing or Erosion of Inner Embankment Slopes	NE	
Upstream Face Slope Protection (HDPE Liner)	NA	
Upstream Face Slope Protection (Riprap)	GC NE	
Animal Damage	NE	
HDPE Liner	NA	
Vegetative Cover	6-0	needs moved
Condition of Piezometers	NA	
Embankment Drainage Ditches	, NA	

ndition Codes

= Emergency Condition. A serious dam safety condition exists that needs immediate action. Report immediately to Chief Dam Safety Engineer and immediate supervisor

= Item needing immediate maintenance to restore or ensure its safety or integrity. Remediation should be completed within 1 month.

f = Item needing minor maintenance. The safety or integrity of the item is not yet imperiled.

= Condition requires regular observation to ensure that the condition does not become worse.

= Good Condition.

= No evidence of a problem.

Not Inspected. Reason should be stated in comment.

Impoundment Bottom Ash Pond

Spillway			
	Drains/Weeps	NA.	
	Discharge coloration	NI	No access
	Seepage	NA	
	Alignment	NA	
	Bridge and Piers	NA	·
	Fencing	NA	
	Construction Joints	NA	
	Trash Racks	NA	
	Differential Settlement	NA	
	Stop Logs	NA	
Energy Dissipator	Riprap	NI	No access
	Outlet Channel	NI	No access
	Concrete Condition	NA	
	Debris	NI	No access
Decant	Alignment	GC	
	Connection to Bollard	6C	
	Debris in Inlets	NE	
	Condition of Pipe	6C	
	Seepage at Inlet or Outlet	NE	

Condition Codes

EC = Emergency Condition. A serious dam safety condition exists that needs immediate action. Report Immediately to Chief Dam Safety Engineer and immediate supervisor

M = Item needing immediate maintenance to restore or ensure its safety or integrity. Remediation should be completed within 1 month.

AM = Item needing minor maintenance. The safety or integrity of the item is not yet imperiled.

DB = Condition requires regular observation to ensure that the condition does not become worse.

3C = Good Condition.

√E = No evidence of a problem.

II = Not inspected. Reason should be stated in comment.